

TEST REPORT

Report No.: BCTC2104648259E

Applicant: Shenzhen SimDisk Technology Co., Ltd.

Product Name: SATA III SSD

Model/Type
reference: SATA

Tested Date: 2021-04-16 to 2021-04-21

Issued Date: 2021-04-21

Shenzhen BCTC Testing Co., Ltd.



Product Name: SATA III SSD
Trademark: N/A
Model /Type Ref.: SATA,
M.2 Satan,M.2 Pcie Ngff,M.2 Pcie Nvme
Prepared For: Shenzhen SimDisk Technology Co., Ltd.
Address: 304, 3rd Floor, No. A, Heping Industrial Park, Changyong Road,
Yucui Community, Longhua Street, Longhua District,
Shenzhen,China
Manufacturer: Shenzhen SimDisk Technology Co., Ltd.
Address: 304, 3rd Floor, No. A, Heping Industrial Park, Changyong Road,
Yucui Community, Longhua Street, Longhua District,
Shenzhen,China
Prepared By: Shenzhen BCTC Testing Co., Ltd.
Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st
Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen,
Guangdong, China
Sample Received Date: 2021-04-16
Sample tested Date: 2021-04-16 to 2021-04-21
Issue Date: 2021-04-21
Report No.: BCTC2104648259E
Test Standards EN 55032:2015/A11:2020, EN 55035: 2017/A11:2020
Test Results PASS

Tested by:



Icey Chen/ Project Handler

Approved by:




Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

TABLE OF CONTENT


Test Report Declaration	Page
1. VERSION	4
2. TEST SUMMARY	5
3. MEASUREMENT UNCERTAINTY	6
4. PRODUCT INFORMATION AND TEST SETUP	7
4.1 Product Information	7
4.2 Test Setup Configuration	7
4.3 Support Equipment	7
4.4 Test Mode	8
5. TEST FACILITY AND TEST INSTRUMENT USED	9
5.1 Test Facility	9
5.2 Test Instrument Used	9
6. RADIATED EMISSIONS TEST	11
6.1 Block Diagram Of Test Setup	11
6.2 Limits	11
6.3 Test Procedure	11
6.4 Test Results	12
7. IMMUNITY TEST OF GENERAL THE PERFORMANCE CRITERIA	14
8. ELECTROSTATIC DISCHARGE (ESD)	15
8.1 Test Specification	15
8.2 Block Diagram of Test Setup	15
8.3 Test Procedure	15
8.4 Test Results	16
9. CONTINUOUS RF ELECTROMAGNETIC FIELD DISTURBANCES (RS)	17
9.1 Test Specification	17
9.2 Block Diagram of Test Setup	17
9.3 Test Procedure	18
9.4 Test Results	18
10. EUT PHOTOGRAPHS	19
11. EUT TEST SETUP PHOTOGRAPHS	21

(Note: N/A means not applicable)



1. VERSION

Report No.	Issue Date	Description	Approved
BCTC2104648259E	2021-04-21	original	Valid



2. TEST SUMMARY

The Product has been tested according to the following specifications:

EMISSION		
Standard	Test Item	Test result
EN 55032	Conducted emissions from the AC mains power ports	N/A ³
EN 55032	Asymmetric mode conducted emissions	N/A ¹
EN 55032	Conducted differential voltage emissions	N/A ²
EN 55032	Radiated emissions	Pass

IMMUNITY (EN 55035)		
Standard	Test Item	Test result
IEC 61000-4-2	Electrostatic discharge (ESD)	Pass
IEC 61000-4-3	Continuous RF electromagnetic field disturbances(RS)	Pass
IEC 61000-4-4	Electrical fast transients/burst (EFT)	N/A ³
IEC 61000-4-5	Surges	N/A ³
IEC 61000-4-6	Continuous induced RF disturbances (CS)	N/A ³
IEC 61000-4-6	Broadband impulse noise disturbances, repetitive	N/A ⁴
IEC 61000-4-6	Broadband impulse noise disturbances, isolated	N/A ⁴
IEC 61000-4-8	Power frequency magnetic field (PFMF)	N/A ⁵
IEC 61000-4-11	Voltage dips and interruptions (DIPS)	N/A ³


Remark:

1. Applicable to ports listed above and intended to connect to cables longer than 3 m.
2. The Product has no antenna port.
3. The EUT is powered by the DC only , the test item is not applicable
4. Applicable only to CPE xDSL ports.
5. The Product doesn't contain any device susceptible to magnetic fields.

3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Test item	Value (dB)
Radiated Emission(30MHz~1GHz)	4.30
Radiated Emission(1GHz~6GHz)	4.90



4. PRODUCT INFORMATION AND TEST SETUP

4.1 Product Information

Ratings: DC 5V from PC

The highest frequency of the internal sources of the EUT is (less than 108)MHz: less than 108 MHz, the measurement shall only be made up to 1 GHz.

between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz.

between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz.

above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 6 GHz, whichever is less.

Cable of Product

No.	Cable Type	Quantity	Provider	Length (m)	Specification	Note
1	--	--	Applicant	---	Shielded	--
2	--	--	BCTC	--	Unshielded	--

4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

4.3 Support Equipment


No	Device Type	Brand	Model	Series No.	Data Cable	Power Cord
1.	PC	Lenovo	ThinkPad S2	---	---	---

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Test Mode

Test item	Test Mode	Test Voltage
Radiated emissions(30MHz-1GHz) Class B	Data transmission	DC 5V from PC
Electrostatic discharge (ESD) B <input checked="" type="checkbox"/> Air Discharge: $\pm 8kV$ <input checked="" type="checkbox"/> Contact Discharge: $\pm 4kV$ <input checked="" type="checkbox"/> HCP & VCP: $\pm 4Kv$ 10 times each point/	Data transmission	DC 5V from PC
Continuous RF electromagnetic field disturbances(RS) A 80MHz-1000MHz,2600MHz,3500MHz,5000MHz, 3V/m,80% AM Front, Rear, Left, Right H/V	Data transmission	DC 5V from PC
All test mode were tested and passed, Radiated Emissions shows (*)is the nearest standard limit which were recorded in this report.		



5. TEST FACILITY AND TEST INSTRUMENT USED

5.1 Test Facility


All measurement facilities used to collect the measurement data are located at BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

5.2 Test Instrument Used

Radiated emissions Test (966 chamber)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	ChengYu	966 Room	966	Jun. 06, 2020	Jun. 05, 2023
Receiver	R&S	ESRP	101154	Jun. 08, 2020	Jun. 07, 2021
Receiver	R&S	ESR3	102075	Jun. 08, 2020	Jun. 07, 2021
Amplifier	Schwarzbeck	BBV9718	9718-309	Jun. 04, 2020	Jun. 03, 2021
Amplifier	Schwarzbeck	BBV9744	9744-0037	Jun. 04, 2020	Jun. 03, 2021
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	VULB9163-942	Jun. 08, 2020	Jun. 07, 2021
Horn Antenna	SCHWARZBECK	BBHA9120 D	1541	Jun. 10, 2020	Jun. 09, 2021
Software	Frad	EZ-EMC	FA-03A2 RE	\	\

Electrostatic discharge Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
ESD Tester	KIKUSUI	KES4201A	UH002321	Jul. 12, 2020	Jul. 10, 2021


Continuous RF electromagnetic field disturbances Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power meter	Keysight	E4419B	GB42421440	Jun. 08, 2020	Jun. 07, 2021
Power sensor	Keysight	E9 300A	US39211305	Jun. 08, 2020	Jun. 07, 2021
Power sensor	Keysight	E9 300A	US39211659	Jun. 08, 2020	Jun. 07, 2021
Amplifier	SKET	HAP_801000M-250W	\	Jun. 04, 2020	Jun. 03, 2021
Amplifier	SKET	HAP_0103G-75W	\	Jun. 04, 2020	Jun. 03, 2021
Amplifier	SKET	HAP_0306G-50W	\	Jun. 04, 2020	Jun. 03, 2021
Stacked double Log.-Per. Antenna	Schwarzbeck	STLP 9129	077	\	\
Field Probe	Narda	EP-601	80256	Jul. 07, 2020	Jul. 06, 2021
Signal Generator	Agilent	N5181A	MY50143748	Jun. 04, 2020	Jun. 03, 2021
Software	SKET	EMC-S	1.2.0.18	\	\



6. RADIATED EMISSIONS TEST

6.1 Block Diagram Of Test Setup

30MHz ~ 1GHz:



6.2 Limits

Limits for radiated disturbance of Class B MME

Frequency (MHz)	Quasi-peak limits at 3m dB(μ V/m)
30-230	40
230-1000	47

Note: The lower limit shall apply at the transition frequencies.


6.3 Test Procedure

30MHz ~ 1GHz:

- The Product was placed on the nonconductive turntable 0.8m above the ground in a semi anechoic chamber.
- Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 120 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.


6.4 Test Results

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	Horizontal
Test Voltage :	DC 5V from PC	Test Mode:	Data transmission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1		44.1202	27.13	-14.59	12.54	40.00	-27.46	QP
2		101.6443	48.51	-15.58	32.93	40.00	-7.07	QP
3		109.4116	48.02	-16.08	31.94	40.00	-8.06	QP
4		201.3930	45.42	-15.23	30.19	40.00	-9.81	QP
5		301.4224	50.72	-12.36	38.36	47.00	-8.64	QP
6	*	993.0114	43.52	-0.98	42.54	47.00	-4.46	QP

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	Vertical
Test Voltage :	DC 5V from PC	Test Mode:	Data transmission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1		50.0566	32.58	-14.08	18.50	40.00	-21.50	QP
2		76.2442	45.46	-18.66	26.80	40.00	-13.20	QP
3		123.2655	42.46	-16.98	25.48	40.00	-14.52	QP
4		201.3930	44.14	-15.23	28.91	40.00	-11.09	QP
5	*	601.4265	42.29	-5.02	37.27	47.00	-9.73	QP
6		801.7863	38.44	-1.95	36.49	47.00	-10.51	QP

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

7. IMMUNITY TEST OF GENERAL THE PERFORMANCE CRITERIA


Product Standard	EN 55035:2017 clause 5
<p>CRITERION A</p>	<p>The equipment shall continue to operate as intended without operator intervention. No degradation of performance, loss of function or change of operating state is allowed below a performance level specified by the manufacturer when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.</p>
<p>CRITERION B</p>	<p>During the application of the disturbance, degradation of performance is allowed. However, no unintended change of actual operating state or stored data is allowed to persist after the test.</p> <p>After the test, the equipment shall continue to operate as intended without operator intervention; no degradation of performance or loss of function is allowed, below a performance level specified by the manufacturer, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance.</p> <p>If the minimum performance level (or the permissible performance loss), or recovery time, is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.</p>
<p>CRITERION C</p>	<p>Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions. A reboot or re-start operation is allowed.</p> <p>Information stored in non-volatile memory, or protected by a battery backup, shall not be lost.</p>

8. ELECTROSTATIC DISCHARGE (ESD)

8.1 Test Specification

Test Port	: Enclosure port
Discharge Impedance	: 330 ohm / 150 pF
Discharge Mode	: Single Discharge
Discharge Period	: one second between each discharge

8.2 Block Diagram of Test Setup



8.3 Test Procedure

- Electrostatic discharges were applied only to those points and surfaces of the Product that are accessible to users during normal operation.
- The test was performed with at least ten single discharges on the pre-selected points in the most sensitive polarity.
- The time interval between two successive single discharges was at least 1 second.
- The ESD generator was held perpendicularly to the surface to which the discharge was applied and the return cable was at least 0.2 meters from the Product.
- Contact discharges were applied to the non-insulating coating, with the pointed tip of the generator penetrating the coating and contacting the conducting substrate.
- Air discharges were applied with the round discharge tip of the discharge electrode approaching the Product as fast as possible (without causing mechanical damage) to touch the Product. After each discharge, the ESD generator was removed from the Product and re-triggered for a new single discharge. The test was repeated until all discharges were complete.
- At least ten single discharges (in the most sensitive polarity) were applied to the Horizontal Coupling Plane at points on each side of the Product. The ESD generator was positioned

vertically at a distance of 0.1 meters from the Product with the discharge electrode touching the HCP.

h. At least ten single discharges (in the most sensitive polarity) were applied to the center of one vertical edge of the Vertical Coupling Plane in sufficiently different positions that the four faces of the Product were completely illuminated. The VCP (dimensions 0.5m x 0.5m) was placed vertically to and 0.1 meters from the Product.

8.4 Test Results

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Test Mode:	Data transmission
Test Voltage :	DC 5V from PC		

Discharge Method	Discharge Position	Voltage (±kV)	Min. No. of Discharge per polarity (Each Point)	Required Level	Performance Criterion
Contact Discharge	Conductive Surfaces	4	10	B	A
	Indirect Discharge HCP	4	10	B	A
	Indirect Discharge VCP	4	10	B	A
Air Discharge	Slots, Apertures, and Insulating Surfaces	8	10	B	A
Note*: N/A					


9. CONTINUOUS RF ELECTROMAGNETIC FIELD DISTURBANCES (RS)

9.1 Test Specification


Test Port	: Enclosure port
Step Size	: 1%
Modulation	: 1kHz, 80% AM
Dwell Time	: 1 second
Polarization	: Horizontal & Vertical

9.2 Block Diagram of Test Setup

Below 1GHz:



Above 1GHz:



9.3 Test Procedure

- a. The testing was performed in a fully-anechoic chamber. The transmit antenna was located at a distance of 3 meters from the Product.
- b. The frequency range is swept from 80MHz to 1000MHz, 1800MHz, 2600MHz, 3500MHz, 5000MHz, with the signal 80% amplitude modulated with a 1 kHz sine wave, and the step size was 1%.
- c. The dwell time at each frequency shall not be less than the time necessary for the EUT to be exercised and to be able to respond, but should not exceed 5 s at each of the frequencies during the scan.
- d. The test was performed with the Product exposed to both vertically and horizontally polarized fields on each of the four sides.
- e. For Broadcast reception function: Group 2 not apply in this test.

9.4 Test Results

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Test Mode:	Data transmission
Test Voltage :	DC 5V from PC		


Frequency	Position	Field Strength (V/m)	Required Level	Performance Criterion
80 - 1000MHz, 1800MHz, 2600MHz, 3500MHz, 5000MHz	Front, Right, Back, Left	3	A	A
Note: N/A				

10. EUT PHOTOGRAPHS


EUT Photo 1




EUT Photo 2



EUT Photo 3



EUT Photo 4



11. EUT TEST SETUP PHOTOGRAPHS


Radiated emissions



ESD



RS



STATEMENT

The equipment lists are traceable to the national reference standards.

The test report can not be partially copied unless prior written approval is issued from our lab.

The test report is invalid without stamp of laboratory.

The test report is invalid without signature of person(s) testing and authorizing.

The test process and test result is only related to the Unit Under Test.

The quality system of our laboratory is in accordance with ISO/IEC17025.

If there is any objection to report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL : 400-788-9558

P.C.: 518103

FAX : 0755-33229357

Internet : <http://www.bctc-lab.com>

E-Mail : bctc@bctc-lab.com.cn

***** END *****